

AW 100

High Pressure Washer



Specifications Voltage (by areas)

Single-phase AC 50/60Hz Voltage 220V to 240V Power Input 1.400W Max Discharge Pressure 7.0MPa (1MPa: 10.2 kgf/cm²) Max Permissible Pressure 10 OMPa

Max Feed Pressure 0.7MPa Max Water Discharge 5.51/min Permissible Temperature 40°C or less Water Feeding Method Faucet connection type Dimensions (L x W x D)*1 305 x 245 x 465mm

Weight*2 Standard Accessories

5.4kg Trigger gun, High-pressure hose (5m), Variable nozzle, Detergent bottle nozzle, Water feed connector, Nozzle cleaner pin. Cord holder. Gun holder. Handle (with 2 attachment screws)

- Vertical type for easy storage
 Built-in thermal protector
 With handle for easy movement

- Rotary ON/OFF switch for convenient use

AW 130

High Pressure Washer



Specifications

Standard Accessories

Voltage (by areas) Single-phase AC 50/60Hz Voltage 220V to 240V Power Input 1.600W Max Discharge Pressure 9.0MPa (1MPa: 10.2 kgf/cm²) Max Permissible Pressure 13 OMPa

Max Feed Pressure 0.7MPa Max Water Discharge 6.0L/min Permissible Temperature Water Feeding Method 40°C or less Faucet connection type Dimensions (L x W x D)*1 Weight*2 325 x 260 x 790mm 8.3kg

Trigger gun, High-pressure hose (10m), Variable nozzle, Turbo nozzle, Detergent bottle nozzle, One-touch joint (black)(For use with the strainer hose), Water feed connector, Nozzle cleaner pin, Cord holder, Handle (with 4

attachment screws)

- Features

 Washing of the wide range is possible with a long
- high-pressure hose

 With wheels and handle for easy movement
- With siphon function
- · Vertical type for easy storage
- Built-in thermal protector
 With handle for easy movement
- Rotary ON/OFF switch for convenient use



*1. Including the handle, power cord holder, gun holder and water feed connector *2. Weight: Excluding the power cord and including trigger gun, high-pressure hos variable nozzle, water feed connector and accessory holder.

AW 150

High Pressure Washer

Features

- Washing of the wide range is possible with a long high-pressure hose
- Variable nozzle (Direct injection / Wide angle) can be used with pressure adjustment
- Large hose reel for convenient storageWith wheels and handle for easy movement
- · With siphon function
- Vertical type for easy storage
- Built-in thermal protectorWith handle for easy movement
- · Rotary ON/OFF switch for convenient use



Specifications Voltage (by areas)

Single-phase AC 50/60Hz Voltage 220V to 240V

2,000W 11.0MPa (1MPa: 10.2 kgf/cm²) Max Discharge Pressure Max Permissible Pressure Max Feed Pressure 15.0MPa 0.7MPa Max Water Discharge Permissible Temperature 6.67L/min 40°C or less

Water Feeding Method Faucet connection type 425 x 345 x 905mm Dimensions (L x W x D)* Weight*2 12.4kg Standard Accessories

Trigger gun, High-pressure hose (10m), Variable nozzle (with pressure adjuster), Turbo nozzle, Detergent bottle (stored

inside the unit), One-touch joint (black) (For use with the strainer hose), Water feed connector, Nozzle cleaner pin, Gun holder, Hose handle, Gun support (with

1 attachment screw)

 ${}^{\star} 1.$ Including the handle, power cord holder, gun holder, gun support and water feed

*2. Weight: Excluding the power cord and including trigger gun, high-pressure hose, variable nozzle, water feed connector and accessory holder.

Power tools catalogue 2021 - 2022 173