

338946

999038 III (110V - 120V) 999065 (220V - 240V)

CS 30SB CS 35SB CS 40SB

300mm/350mm/ 400mm Chain Saws



Features

- Built-in tool-less chain adjuster with a large tension dial and knob
- Chain oil flow adjuster to adjust the chain oil flow rate for auto lubrication
- Rear handle with soft grip



220V. 230V. 240V Voltage Power Input 1,900W 14.5m/s No Load Chain Speed Chain Pitch 3/8" 0.05" Chain Gauge Guide Bar Length: CS30SB CS35SB 350mm 400mm Type of Guide Bar Sprocket Nose

Oil Tank Capacity 200mL 445 x 270 x 198mm Dimensions (L x W x H) Dry Weight*: CS30SB CS35SB 4.7kg

4.8kg 4.9kg Guide Bar, Saw Chain, Chain Saw Oil Standard Accessories



* Weight according to EPTA-Procedure 01/2003.

CS 30Y CS 35Y CS 40Y CS 45Y

300mm/350mm/ 400mm/450mm **Chain Saws**



- Balanced design for more control
- Tool-less chain adjuster
 Large switch lever with soft start and over-load protection

 • Chain oil flow adjuster
- Front and rear handles with soft grip

Specifications

Voltage Power Input 110V 1,560W 220V. 230V, 240V 2,000W 14.5m/s No Load Chain Speed 3/8" Chain Pitch Chain Gauge Guide Bar Length : CS30Y CS35Y 300mm 350mm CS40Y CS45Y 400mm 450mm Type of Guide Bar Oil Tank Capacity Sprocket Nose 150mL Dimensions (L x W x H)
Dry Weight* : CS30Y 490 x 217 x 220mm 5.3kg 5.4kg 5.5kg CS35Y CS40Y 5.6kg Guide Bar, Saw Chain, Plug Clip Chain CS45Y Standard Accessories









* Weight includes guide bar and saw chain. According to EPTA-Procedure 01/2003.