

## GB 18 LTX BL Q I (603828500) Cordless Tappers

18V 2x5.2Ah Li-ion; Charger ASC 55 (220-240 V / 50 - 60 Hz); metaBOX 145 L

Order no. 603828500

EAN 4007430333599



Product may differ from image



- High-grade cordless drill/screwdriver with unique, patented thread-tapping function
- Quick and interruption-free cutting and cleaning of threads thanks to automatic change of direction of rotation
- Two quick-change tapping chuck for inserting taps with square and cylindrical shanks
- Metabo "Quick" System: quick change of bit retainer and bits for flexible working
- Unique Metabo brushless motor for quick work progress and highest efficiency when drilling and screwdriving
- Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces
- Precision Stop: electronic torque control with increased precision for accurate and intricate working
- Overload protection: protects the motor from overheating
- Spindle with hexagonal recess for screwdriver bits for working without chuck
- Collar (Ø 43 mm) for versatile use
- Integrated working light to illuminate the contact area
- Robust die cast aluminium gear housing for optimum heat dissipation and long service life
- Handy belt hook and bit holder can be fixed either on the right or left side
- With metaBOX, the intelligent solution for transport and storage
- Can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-system.com](http://www.cordless-alliance-system.com)

## Technical data

### Characteristics

Type of battery pack	Li-ion
Battery voltage	18 V
Battery pack capacity	2 x 5.2 Ah
Maximum torque - soft	60 Nm / 531 in-lbs
Maximum torque, hard	120 Nm / 1062 in-lbs
Adjustable torque	1 - 20 Nm // 9 - 177 in-lbs
Max. thread diameter	M4 - M12
Drill Ø steel	13 mm / 1/2 "
Drill-Ø soft wood	65 mm / 2 1/2 "
No-load speed	0 - 500 / 0 - 1850 rpm
Chuck capacity	1.5 - 13 mm // 1/32 - 1/2 "
Weight (including battery pack)	2.5 kg / 5.5 lbs

### Vibration

Drilling in metal	3.2 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

### Noise emission

Sound pressure level	78 dB(A)
Sound power level (LWA)	89 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Quick-change tapping chuck M4-M6  
 Belt hook and bit case  
 2 Li-Power battery packs (18 V/5.2 Ah)  
 Charger ASC 55 "AIR COOLED"  
 metaBOX 145 L  
 Quick-change tapping chuck M8-M12  
 Side handle